

Tabletop Vending with Thermoelectric Cooling System

UnoCool is SandenVendo's tabletop snack dispenser designed to meet the demands of a clientele with limited space availability, who aspire to deliver temperature-sensitive products.

Load all your favorite drinks and snacks in this new eco-friendly device: UnoCool is our first vending solution powered by a Thermoelectric Cooler (TEC) that cools products up to a minimum of 8° C.

Compact and space-saving, UnoCool is the perfect vending solution for venues such as pubs, office spaces, meeting rooms, sports facilities and hotel receptions



SUC

UnoCool Tabletop

	SUC
AFMETINGEN H x B x D (mm)	800 x 590 x 620
GEWICHT (NETTO/BRUTO: standaard zonder opties)	70 Kg / 75 Kg
AANTAL SELECTIES PER PLATEAU	4
AANTAL PLATEAUS	Standard 3 / Max. 4
AANTAL SELECTIES	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
KOEL SYSTEEM	Thermoelectric
TEMPERATUURCONTROLE	Delta T=12°C vs. T Ambiente
INTERN TEMPERATUURBEREIK	10°C
MAX. VERBRUIK	120 W
ELEKTRISCHE VOEDING	220 V / 50 Hz
ENERGIEVERBRUIK - kWh/annum	841

Tabletop Vending with Thermoelectric Cooling System

UnoCool is SandenVendo's tabletop snack dispenser designed to meet the demands of a clientele with limited space availability, who aspire to deliver temperature-sensitive products.

Load all your favorite drinks and snacks in this new eco-friendly device: UnoCool is our first vending solution powered by a Thermoelectric Cooler (TEC) that cools products up to a minimum of 8° C.

Compact and space-saving, UnoCool is the perfect vending solution for venues such as pubs, office spaces, meeting rooms, sports facilities and hotel receptions



SCS

UnoCool Tabletop Slave

	SCS
AFMETINGEN H x B x D (mm)	800 x 475 x 620
GEWICHT (NETTO/BRUTO: standaard zonder opties)	59 Kg / 65 Kg
AANTAL SELECTIES PER PLATEAU	4
AANTAL PLATEAUS	Standard 3 / Max. 4
AANTAL SELECTIES	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
KOEL SYSTEEM	Thermoelectric
TEMPERATUURCONTROLE	Delta T=12°C vs. T Ambiente
INTERN TEMPERATUURBEREIK	10°C
MAX. VERBRUIK	120 W
ELEKTRISCHE VOEDING	220 V / 50 Hz
ENERGIEVERBRUIK - kWh/annum	841